

High Speed & Reliable 24-Pin Narrow / Wide Carriage Flatbed Impact Printer



DP560

High Speed & Reliable 24-Pin Narrow
Wide Carriage Flatbed Impact Printer

Highlights:

- Print width: 82 Columns
- Fast printing speed: 420CPS
- Better connectivity with:
USB2.0 Full-speed & Paralled interaface
- Optional interfaces:
Buluetooth/Wi-Fi/Ethernet
- Original + 6 copies

High Speed & Reliable 24-Pin Narrow / Wide Carriage Flatbed Impact Printer



Specification:

Print type	24-pin impact dot matrix		
Print direction	Bi-directional with logic seeking		
Print width	82 column(10cpi/208.3mm)		
Print speed(10CPI)	Super high speed	420	CPS
	High speed	300	CPS
	Normal speed	150	CPS
Fonts	Draft, Roman, Sans Serif, Courier, Prestige, Script, OCR-A, OCR-B		
Bar code	EAN-13, EAN-8, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5, Code 39, Code 128 B, Code 128 C, Codabar		
Character pitch	ASCII:10CPI , 12CPI,15CPI,proportional		
Line space	1/6 inch,1/8 inch, programmable in 1/360 inch increments		
Emulation	EPSON ESC/PK2, OKI 5530SC, IBM 2391		
Interface	U USB 2.0	S Serial	DP560 U P DP560W U P W
	P Parallel	E Ethernet	DP560E U P E DP560S U S
	B Bluetooth		
	W Wi-Fi: 802.11b/g/n		DP560B U P B
Buffer Memory	256 KB		
Ribbon	Model Life JMR 139		
	Life(draft mode) > 10 million characters		
Noise	< 55dB(A)(ISO7779 standard)		
Paper feed type	Cut sheet Front in, front out; front in, rear out		
	Tractor paper Rear in, front out		
Paper specification	Cut sheet Width:55-297mm Length:67-536mm		
	Tractor paper Width:60-272mm		

Transverse certificate(Lay open)	Width:90-297mm Length:75-300mm
	Thickness:1.8mm
Max paper thickness	2.0mm
Copy	Original + 6 copies
Compress printing	Support graphics and character compression printing, compression ratios are 50%, 66%, 75%, 100%, auto compress printing, select this function in the menu.
Adaptive application	Paper edge detection, skew detection, black mark detection, paper thickness auto-adaptation, Full slot paper feeding, copy capacity auto adjustment
Special function	Pin Break Compensation, Pin Rotation Replacement, Automatic Emulation Match, Online Parameter Setting
Dimension	422mm(W) x 239mm(D) x 200mm(H)
Weight	Approx. 4.9KG
Environmental conditions	
Operating	Working temperature: 5~40 C Humidity: 25~80%RH(No condensation)
Storage	Storage temperature: -40~55 C Humidity: ≤93%RH(40 C, No condensation)
Power supply	
Rated voltage	220V
Rated frequency range	50Hz
Safety marks	GB4943 / EN60950
Certificate	



EN60950

Note: 1. The technical specifications in this catalog are the laboratory measurement data which achieved under the national standard for the storage and work environment (room temperature), the specifications of the testing papers are specified in the Users' Manual.
2. The technical specifications are subject to change without notice.
3. All trademarks are the properties of their respective holders.

Jolimark[®]

Address: Unit 01, 23A/F, K.Wah Centre, 191 Java Road, North Point, Hong Kong

Tel: (852) 25582457

Fax: (852) 28979610

Email: sales@kongyue.com.hk

Http://www.jolimark.com/en